

KENWOOD

ACCESSORY PRICE GUIDE November 2025 Edition



American Communication Systems

Discover the Power of Communications™

<http://www.ameradio.com>



Optional Accessories for Kenwood Portables

ANTENNAS		NX-5200/5300	NX-5400	NX-3200/3300	NX-3400	NX-3220/3320	NX-3420	NX-1200/1300	NX-1202/1302	PKT-300
KRA-26M	VHF helical antenna 146-162 MHz	•	-	•	-	•	-	•	•	-
KRA-26M2	VHF helical antenna 162-174 MHz	•	-	•	-	•	-	•	•	-
KRA-26M3	VHF helical antenna 136-150 MHz	•	-	•	-	•	-	•	•	-
KRA-27M	UHF whip antenna 440-490 MHz	•	-	•	-	•	-	•	•	-
KRA-27M2	UHF whip antenna 470-520 MHz	•	-	•	-	•	-	•	•	-
KRA-27M3	UHF whip antenna 400-450 MHz	•	-	•	-	•	-	•	•	-
KRA-22M	VHF low-profile helical antenna 148-162 MHz	•	-	•	-	•	-	•	•	-
KRA-22M2	VHF low-profile helical antenna 162-174 MHz	•	-	•	-	•	-	•	•	-
KRA-22M3	VHF low-profile helical antenna 136-150 MHz	•	-	•	-	•	-	•	•	-
KRA-23M	UHF low-profile helical antenna 450-490 MHz	•	-	•	-	•	-	•	•	-
KRA-23M2	UHF low-profile helical antenna 470-520 MHz	•	-	•	-	•	-	•	•	-
KRA-23M3	UHF low-profile helical antenna 403-430 MHz	•	-	•	-	•	-	•	•	-
KRA-41M	VHF stubby antenna 148-162 MHz	•	-	•	-	•	-	•	•	-
KRA-41M2	VHF stubby antenna 162-174 MHz	•	-	•	-	•	-	•	•	-
KRA-41M3	VHF stubby antenna 136-150 MHz	•	-	•	-	•	-	•	•	-
KRA-42M	UHF stubby antenna 440-490 MHz	•	-	•	-	•	-	•	•	-
KRA-42M2	UHF stubby antenna 470-520 MHz	•	-	•	-	•	-	•	•	-
KRA-42M3	UHF stubby antenna 403-430 MHz	•	-	•	-	•	-	•	•	-
KRA-25	High gain VHF helically loaded whip antenna 148-162 MHz	•	-	•	-	•	-	•	•	-
KRA-28	Broad-band VHF helically loaded whip antenna 140-170 MHz	•	-	•	-	•	-	•	•	-
KRA-29	Broad Band UHF Whip Antenna 380-430 MHz	•	-	•	-	•	-	•	•	-
KRA-32K	700/800 MHz Whip Antenna	-	•	-	•	-	•	-	-	-
KRA-36	700/800 MHz Stubby Antenna	-	•	-	•	-	•	-	-	-
KRA-38K	800/900 MHz Whip Antenna	-	-	-	•	-	•	-	-	-
KRA-39	900 MHz Stubby Antenna	-	-	-	•	-	•	-	-	-
BATTERIES		NX-5200/5300	NX-5400	NX-3200/3300	NX-3400	NX-3220/3320	NX-3420	NX-1200/1300	NX-1202/1302	PKT-300
KNB-L1M	Li-ion 2000mAh, IP67/68 (Compact Slim)	•	•	-	-	-	-	-	-	-
KNB-L2M	Li-ion 2600mAh, IP67/68 (Standard)	•	•	-	-	-	-	-	-	-
KNB-L11M	Li-ion 3900mAh, IP67/68 (High Capacity) Note: The KNB-L11 battery requires NX-5x00 firmware 5.12 or newer	•	•	-	-	-	-	-	-	-
KNB-L12M	Laminated Li-ion 3000mAh (High Capacity)	•	•	-	-	-	-	-	-	-
KNB-L13M	Laminated Li-ion 4000mAh (High Capacity)	•	•	-	-	-	-	-	-	-
KNB-LS5CU	CSA US Intrinsically Safe Battery Li-ion 2000mAh, IP67/68 [Intrinsically Safe Option]	•	•	-	-	-	-	-	-	-
KNB-LS7M	CSA US Intrinsically Safe Battery Li-ion 3800mAh, IP67/68 [Intrinsically Safe Option]	•	•	-	-	-	-	-	-	-
KBP-8M2	AA Alkaline Rechargeable Battery Pack (12 AA; 9V). Cells not included. Note: The color of the case is International Orange.	-	•	-	-	-	-	-	-	-
KNB-78LM	2860 mAh, Li-ion battery, IP67, battery only, best for trunked mode operation	-	-	•	•	•	•	-	-	-
KNB-57LAM	2000 mAh, Li-ion battery, IP67, battery only, best for conventional mode operation	-	-	•	•	•	•	-	-	-
KNB-55LAM	1480 mAh, Li-ion battery, IP67, battery only	-	-	•	•	•	•	-	-	-
KNB-56N	1400 mAh, Ni-MH battery, IP67, battery only	-	-	•	•	•	•	-	-	-
KNB-79LCM	CSA US Intrinsically Safe Battery Li-ion 2860mAh, IP67, battery only [Intrinsically Safe Option]	-	-	•	•	•	•	-	-	-
KBP-5	AA Alkaline Rechargeable Battery Pack (6 AA; 9V) cells not included	-	-	•	•	•	•	-	-	-
KNB-45J	2000 mAh, Li-ion battery - requires KSC-35K/SK charger	-	-	-	-	-	-	•	•	-
KNB-45LK	2000 mAh, Li-ion battery - requires KSC-35K/SK charger	-	-	-	-	-	-	•	•	-
KNB-69L	2550 mAh, Li-ion battery - requires KSC-35K/SK charger	-	-	-	-	-	-	•	•	-
KNB-82LCM	CSA US Intrinsically Safe Battery Li-ion 1900mAh, battery only [Intrinsically Safe Option - NOT include NX-1200/1300 Analog and K3/K6 models]	-	-	-	-	-	-	•	-	-
KNB-29N	1500 mAh, NiMH battery - requires KSC-43K charger	-	-	-	-	-	-	•	•	-
KNB-84LLA	1900 mAh, Li-ion battery (IEC 60529 - IP67) - requires KSC-35K/SK charger Note: IP67 is only available with NX-1200/1300 K3 and K6 models	-	-	-	-	-	-	•	-	-
KNB-84LM	1900 mAh, Li-ion battery (IEC 60529 - IP67) - requires KSC-35K/SK charger Note: IP67 is only available with NX-1200/1300 K3 and K6 models	-	-	-	-	-	-	•	-	-
KNB-81LW	Li-ion battery (Same as supplied with PKT-300K)	-	-	-	-	-	-	-	-	•

Optional Accessories for Kenwood Portables

CHARGERS		NX-5200/5300	NX-5400	NX-3200/3300	NX-3400	NX-3220/3320	NX-3420	NX-1200/1300	NX-1202/1302	PKT-300
KSC-Y32K	Rapid rate single unit charger (Long-Life Charge Mode capable with KAS-12 Software) <i>Note:</i> NOT compatible with the KNB-L11 battery	•	•	-	-	-	-	-	-	-
KSC-52BK	Rapid rate single unit charger for KNB-L1/KNB-L2/KNB-L3/KNB-L55/KNB-LS7/KNB-33L/PB-45L/KNB-47L/KNB-48L/KNB-72L/C/KNB-70LEX/KNB-41INC/KNB-50NC/KNB-54N	•	•	-	-	-	-	-	-	-
KSC-52AK	Rapid rate single unit charger for the new KNB-L11 high capacity battery	•	•	-	-	-	-	-	-	-
KSC-526K	Rapid rate 6-unit charger CEC Compliant <i>Note:</i> Requires charging pocket/KSC-52PBW and/or KSC-52PCW, and/or KSC-52PAW	•	•	•	•	•	•	-	-	-
KSC-52PBW	Charging pocket for KSC-526K and/or to convert the pocket style of a KSC-52 Single unit charger compatible with the KNB-L1, L2, L3, LS5 and LS7 batteries, and NX-205/305 and NX-210 series	•	•	-	-	-	-	-	-	-
KSC-52PAW	Charging pocket for KSC-526K and/or to convert the pocket style of a KSC-52 Single unit charger compatible with the KNB-L11 battery	•	•	-	-	-	-	-	-	-
KMB-526K	Wall Mount Bracket for KSC-526K	•	•	•	•	•	•	-	-	-
KVC-15	Rapid rate DC vehicular charger adapter for the KSC-32 (chargers not included; includes KSC-mobile bracket & cigarette lighter cable DC adapter) <i>Note:</i> NOT compatible with KSC-52BK or KSC-52AK	•	•	-	-	-	-	-	-	-
KVC-52	Rapid rate DC vehicular charger adapter for the KSC-52BK/52AK chargers (chargers not included; includes steel mounting base & locking bracket, and DC cable with a fused cigarette lighter plug)	•	•	-	-	-	-	-	-	-
KVC-23	Rapid rate DC vehicular charger for TK-5x10/5x20, NX-5x00/x00/x10/x20, TK-x180, TK-x170, & TK-x360 portables with Lithium Ion/Lithium Polymer/NiMH packs only <i>Note:</i> NOT compatible with KNB-L11 battery	•	•	•	•	•	•	-	-	-
KVC-23A	Rapid rate DC vehicular charger for TK-5x10/5x20, NX-5x00/x00/x10/x20, TK-x180, TK-x170, & TK-x360 portables with Lithium Ion/Lithium Polymer/NiMH packs only <i>Note:</i> NOT compatible with KNB-L11 battery	•	•	•	•	•	•	-	-	-
KVC-4	Vehicular charger adapter for the KSC-16/18/20/24/25SK chargers	-	-	•	•	•	•	-	-	-
KSC-25LSK	100-240 volt rapid rate single unit charger for KNB-40LC(V)/55L/57L/68LC/78LM/79LCM Li-Ion Battery	-	-	•	•	•	•	-	-	-
KSC-25SK	110 volt Rapid rate single unit charger for KNB-26N/40LC(V)/55L/56N/57L/68LC/78LM/79LCM	-	-	•	•	•	•	-	-	-
KMB-16	Six Unit Charger Adapter for the KSC-16/20/24/25/25L chargers (chargers not included)	-	-	•	•	•	•	-	-	-
KMB-23	Six Unit Charger Adapter for the KSC-16/20/24/25/25L/32 chargers (chargers not included)	-	-	•	•	•	•	-	-	-
KSC-52PCW	Charging pocket for KSC-526K compatible with NX-3000 series	-	-	•	•	•	•	-	-	-
KSC-35SK	110-220 volt Fast rate single unit charger for KNB-45L/69L	-	-	-	-	-	-	•	•	-
KSC-43K	110-220 volt Fast rate single unit charger for KNB-29N/45L/69L	-	-	-	-	-	-	•	•	-
KMB-28AK	Six Unit Charger Adapter for the KSC-35SK chargers (chargers not included) <i>Note:</i> A supplied in-line AC-DC switching power supply with six DC plugs supply installed KSC-xx charger bases. This unit is lower profile and less weight than similar Kenwood six unit charger adapters.	-	-	-	-	-	-	•	•	-
KVC-22	110-220 volt Fast rate DC vehicular charger adapter for KSC-35SK charger (charger not included)	-	-	-	-	-	-	•	•	-
KSC-50K	Li-Ion Rapid rate charger (Same as supplied with PKT-300K)	-	-	-	-	-	-	-	-	•
KSC-44MLKS	AC Adapter (For cradle multi unit use, up to 6 units)	-	-	-	-	-	-	-	-	•
KSC-506K	Rapid rate 6-Unit Charger for KNB-81L	-	-	-	-	-	-	-	-	•

Optional Accessories for Kenwood Portables

CARRYING ACCESSORIES		NX-5200/5300	NX-5400	NX-3200/3300	NX-3400	NX-3220/3320	NX-3420	NX-1200/1300	NX-1202/1302	PKT-300
KBH-11	Spring action belt clip (2.5")	•	•	•	•	•	•	-	-	-
KBH-8DS	Leather swivel belt loop with portable D-Ring attachment	•	•	•	•	•	•	•	•	•
KLH-6SW	Leather swivel belt loop / detachable swivel D-Ring back	•	•	-	-	-	-	-	-	-
KLH-137ST	Firemen's Heavy-Duty Leather Shoulder Strap for a Heavy-Duty Leather Case	•	•	-	-	-	-	-	-	-
KLH-200K3	Heavy duty leather carrying case for NX-5000 series with KNB-L1/L2/L3/LS5CU (for both keypad models)	•	•	-	-	-	-	-	-	-
KLH-201K3	Nylon carrying case for NX-5000-series with KNB-L1/L2/L3/LS5CU (for both keypad models)	•	•	-	-	-	-	-	-	-
KLH-206K	Heavy-Duty Leather Case w/Swivel Belt Loop for Basic Model	-	-	•	-	•	-	-	-	-
KLH-206K2	Heavy-Duty Leather Case w/Swivel Belt Loop for Standard Keypad Model	-	-	•	-	•	-	-	-	-
KLH-206K3	Heavy-Duty Leather Case w/Swivel Belt Loop for Full Keypad Model	-	-	•	•	•	•	-	-	-
KLH-207K	Nylon carrying case for Basic Model	-	-	•	-	•	-	-	-	-
KLH-207K2	Nylon carrying case for Standard Keypad Model	-	-	•	-	•	-	-	-	-
KLH-207K3	Nylon carrying case for Full Keypad Model	-	-	•	•	•	•	-	-	-
KBH-10	Spring action belt clip	-	-	-	-	-	-	•	•	-
KLH-187	Nylon case for NX-1200/1300 srs	-	-	-	-	-	-	•	•	-
KBH-23M	Belt Clip Holster (Same as supplied with PKT-300K)	-	-	-	-	-	-	-	-	•
KBH-21W	Belt Clip	-	-	-	-	-	-	-	-	•
MICROPHONES & AUDIO ACCESSORIES		NX-5200/5300	NX-5400	NX-3200/3300	NX-3400	NX-3220/3320	NX-3420	NX-1200/1300	NX-1202/1302	PKT-300
KMC-70M	MIL-SPEC, IP54/55/67/68* Speaker Mic with Active Noise Reduction . Note: IP68 is available only when used with NX-5000 series portable. [Intrinsically Safe Option]	•	•	•	•	-	-	-	-	-
KMC-72W	MIL-SPEC, IP54/55/67 Noise-cancelling Speaker Mic [Intrinsically Safe Option]	•	•	•	-	-	-	-	-	-
KMC-49	MIL-SPEC, Speaker Mic, with Antenna Connector Note: 5/16" Coax cable hex wrench included (antenna is not included). [Intrinsically Safe Option]	•	•	-	-	-	-	-	-	-
KEP-1	3.5mm earphone kit for KMC-41/42W/54W/70M/72W Speaker Mics [Intrinsically Safe Option]	•	•	•	•	-	-	-	-	-
KEP-2	2.5mm earphone kit for KMC-49/17/45 Speaker Mic [Intrinsically Safe Option]	•	•	-	-	•	•	•	•	•
KCT-51	Hirose 6-pin Adapter (adapts KVL/aftermarket audio acc. to portable connector) [Intrinsically Safe Option]	•	•	-	-	-	-	-	-	-
KHS-11BL	2-wire palm mic w/earphone, universal connector (Black) [Intrinsically Safe Option]	•	•	•	•	-	-	-	-	-
KHS-12BL	3-wire mini lapel mic w/earphone, universal connector (Black) Note: NOT compatible with TDMA operations [Intrinsically Safe Option]	•	•	•	•	-	-	-	-	-
KHS-14C	Lt. Wt. Single muff headset w/boom mic & In-line PTT Note: Operating & Storage temperature is -4°F to 122°F (-20°C to 50°C)	•	•	•	•	-	-	-	-	-
KHS-15D-BH	Hvy-duty noise reduction behind-the-headset w/noise cancelling boom mic & PTT [Intrinsically Safe Option]	•	•	•	•	-	-	-	-	-
KHS-15DC-BH	Hvy-duty behind-the-headset w/boom mic & earcup-mounted PTT with NRR of 24dB [Intrinsically Safe Option]	•	•	•	•	-	-	-	-	-
KHS-15D-OH	Hvy-duty noise reduction over-the-headset w/noise cancelling boom mic & PTT [Intrinsically Safe Option]	•	•	•	•	-	-	-	-	-
KMC-40	MIL-SPEC, Speaker Mic, with Antenna Connector Note: 5/16" Coax cable hex wrench included (antenna is not included). [Intrinsically Safe Option]	-	-	•	•	-	-	-	-	-
KMC-45D	MIL-SPEC, IP54/35 Speaker microphone (Built-in 2.5mm miniature earphone jack) Note: KMC-45 (Non-D version) is not compatible with DMR (TDMA) operation. [Intrinsically Safe Option]	-	-	-	-	•	•	•	•	•
KMC-21A	Compact speaker microphone [Intrinsically Safe Option]	-	-	-	-	•	•	•	•	•
KHS-7C	Single muff headset w/boom mic no PTT Note: Operating & Storage temperature is -4°F to 122°F (-20°C to 50°C)	-	-	-	-	•	•	•	•	•
KHS-7AC	Lt. Wt. Single muff headset w/boom mic & in-line PTT Note: Operating & Storage temperature is -4°F to 122°F (-20°C to 50°C)	-	-	-	-	•	•	•	•	•

Optional Accessories for Kenwood Portables

KHS-8BL	Two-Wire palm mic wearphone (black) [Intrinsically Safe Option]	-	-	-	-	•	•	•	•	•
KHS-9BL	Three-Wire lapel mic wearphone (black) Note: Available for Analog and NXDN (FDMA) only. NOT compatible with DMR (TDMA) operations.	-	-	-	-	•	•	•	•	•
KHS-10D-BH	Hvy-duty noise reduction behind-the-headset whoise cancelling boom mic & in-line PTT [Intrinsically Safe Option]	-	-	-	-	•	•	•	•	•
KHS-10D-OH	Hvy-duty noise reduction over-the-headset whoise cancelling boom mic & in-line PTT [Intrinsically Safe Option]	-	-	-	-	•	•	•	•	•
KHS-10DC-BH	Hvy-duty Behind-the-head Headset W/boom Mic Earcup-mounted PTT with NRR of 24dB [Intrinsically Safe Option]	-	-	-	-	•	•	•	•	•
KHS-10DC-OH	Hvy-duty Over-the-head Headset W/boom Mic Earcup-mounted PTT with NRR of 24dB [Intrinsically Safe Option]	-	-	-	-	•	•	•	•	•
KHS-22A	Behind-the-Head Headset with flexible boom mic and in-line PTT single ear receiver (low profile wire head band) [Intrinsically Safe Option]	-	-	-	-	•	•	•	•	•
KHS-26	Clip Mic wearphone	-	-	-	-	•	•	•	•	•
KHS-27A	D-Ring Ear Hanger w/PTT & Mic	-	-	-	-	•	•	•	•	•
KHS-31C	C-Ring Ear Hanger w/PTT & Mic	-	-	-	-	•	•	•	•	•
OTHERS		NX-5200/5300	NX-5400	NX-3200/3300	NX-3400	NX-3220/3320	NX-3420	NX-1200/1300	NX-1202/1302	PKT-300
KWD-YH-5000	Yellow Housing Kit for NX-5000 series Portables (Standard Key Model K2/K5 Only) Order L-5024 for Factory Install. (Eligible for warranty of IP67/68 immersion / Intrinsically Safe Option must be installed by Kenwood.)	•	•	-	-	-	-	-	-	-
KWD-AE30K	AES FIPS140-2 Level 1 & DES Encryption Module (Multi-Key) Order a Labor Code L-5003 if installation is required. (Eligible for warranty of IP67/68 immersion / Intrinsically Safe Option must be installed by Kenwood. If you order only a Module and perform Dealer Installation, IP67/68 Warranty Claim will not be eligible.) KWD-AE30K requires a Motorola KVL-3000 Plus/4000 key loader device. KWD-AE30K is an U.S. DOC/BIS Export Controlled Item (ECCN 5A002A.1). Note: Required for Link Layer Authentication	•	•	-	-	-	-	-	-	-
KWD-AE31K	[Intrinsically Safe Option]. Must be Kenwood installed for I.S. AES & DES Encryption Module (Multi-Key) Order a Labor Code L-5004 if installation is required. (Eligible for warranty of IP67/68 immersion / Intrinsically Safe Option must be installed by Kenwood. If you order only a Module and perform Dealer Installation, IP67/68 Warranty Claim will not be eligible.) Note: Requires KPG-AE10E1 software key loader or Motorola KVL-3000 Plus/4000 key loader device. KWD-AE31K is an U.S. DOC/BIS Export Controlled Item (ECCN 5A002A.1) Note: Required for Link Layer Authentication	•	•	-	-	-	-	-	-	-
KCT-48VU	[Intrinsically Safe Option]. Must be Kenwood installed for I.S. External Vibration Unit Note: Audio accessories cannot be used when this option installed. KCT-48VU does not support the P25 digital mode calling or paging features	•	•	•	•	-	-	-	-	-
KPG-36XM	[Intrinsically Safe Option] Full Speed USB Programming interface cable Note: This cable with USB mode may used for SD Card Direct Access.	•	•	•	•	-	-	-	-	-
KPG-93	Encryption Key Loader Interface Cable for Motorola KVL-3000/3000 Plus/4000	•	•	-	-	-	-	-	-	-
KPG-93AUT	KVL-4000 Radio Authentication Cable Note: Only capable for P25 Radio Authentication. Not available for Encryption Key Loading.	•	•	-	-	-	-	-	-	-
KPG-CLN-14P	Portable-to-Portable Cloning Cable (14P:14P), 1m	•	•	-	-	-	-	-	-	-
KWD-YH-3000U	High Visibility Green Housing Kit for NX-3x00 series Standard Key Portables Must order L-5068 for Factory Install. Eligible for warranty of IP67 immersion only when factory installed with L-5068. Note: If you order only housing and perform Dealer Installation, IP67 Warranty Claim will not be eligible.	-	-	•	-	-	-	-	-	-
KWD-YH-3000P	High Visibility Green Housing Kit for NX-3x20 series Standard Key Portables Must order L-5068 for Factory Install. Eligible for warranty of IP67 immersion only when factory installed with L-5068. Note: If you order only housing and perform Dealer Installation, IP67 Warranty Claim will not be eligible. Note: Coloring of housing changed to High Visibility Green after Nov 2021 production. Original yellow	-	-	-	-	•	-	-	-	-
KPG-22UM	USB Programming interface cable	-	-	-	-	•	•	•	•	•
E30-3410-05	2 pin Clone Cable	-	-	-	-	-	-	•	•	•
D32-0456-03	Channel stopper for NX-1000 series Basic(No Display) model	-	-	-	-	-	-	•	•	•

Optional Accessories for Kenwood Mobiles

MICROPHONES AND SPEAKERS		NX-5700/5800/5900	NX-5700H/5800H	NX-5600H	NX-3720HG/3820HG	NX-3920G/3921G	NX-1700/1800
KMC-65M	MIL-SPEC Standard electret mobile microphone (8-pin mod. plug)	•	•	•	•	•	•
KMC-66M	MIL-SPEC Standard electret mobile microphone with 12 keypad (8-pin mod. plug)	•	•	•	•	•	•
KES-8K	External speaker, 10W, 4-Ohm, 3.5mm phone plug	•	-	-	•	•	•
KES-5A	External speaker, 40W max input Note: Requires KCT-72M to connect to Remote Control Head	•	•	•	•	•	•
KMC-9C	Control Station Desktop Microphone (8-pin mod. plug) Note: NOT compatible with TDMA operations	•	•	•	•	•	•
KMC-59C	Control Station Desktop Microphone (8-pin mod. plug) Note: Compatible with FDMA (analog / NXDN) and TDMA (DMR) Operation	•	•	•	•	•	•
DC POWER CABLES		NX-5700/5800/5900	NX-5700H/5800H	NX-5600H	NX-3720HG/3820HG	NX-3920G/3921G	NX-1700/1800
KCT-23M	DC Cable, 35-50W, 10 feet	•	-	-	•	•	•
KCT-23M3	DC Cable, 35-50W, 23 feet	•	-	-	•	•	•
KCT-23M2	DC Cable, 75-110W, 10 feet	-	•	•	-	-	-
KCT-23M4	DC Cable, 75/110W, 23 feet	-	•	•	-	-	-
MOUNTING BRACKETS		NX-5700/5800/5900	NX-5700H/5800H	NX-5600H	NX-3720HG/3820HG	NX-3920G/3921G	NX-1700/1800
KMB-33M	Mounting Bracket Note: For mid power mobiles (NX-5700/5700B/5800/5800B/5900/5900B) only.	•	-	-	-	-	-
KMB-36	Mounting Bracket Note: For high power mobiles (NX-5600H/5700H) only.	-	•	•	-	-	-
CONTROL STATION INSTALLATION ACCESSORIES		NX-5700/5800/5900	NX-5700H/5800H	NX-5600H	NX-3720HG/3820HG	NX-3920G/3921G	NX-1700/1800
KMB-34	Control Station Mounting Case for KPS-15 Power Supply and Mobiles (excludes TK-5x10/6110 series). (mobile mounting hardware included)	•	-	-	•	•	•
KPS-15	DC Switching Power Supply (117/230 VAC; 23A max. continuous, 25A peak)	•	-	-	•	•	•
CONTROL HEADS		NX-5700/5800/5900	NX-5700H/5800H	NX-5600H	NX-3720HG/3820HG	NX-3920G/3921G	NX-1700/1800
KCH-19M	Basic Control Panel	•	•	•	-	-	-
KRK-14HM	Control Head Interface Kit for KCH-19M	•	•	•	-	-	-
KCH-20RM	Full Featured Remote Control Panel Note: - Remote configuration only. No Internal Speaker included. KES-5A is required. - microSD License (KWD-5002SD) and Bluetooth SPP License (KWD-5003BT) are NOT required for both KCH-20RM and connected RF Decks. KCH-20RM and connected RF Decks can be used of microSD and Bluetooth SPP with NO License Activation.	•	•	•	-	-	-
KCH-21RM	Hand Held Control Head for Long Cable *Requires KCT-77M2 (17 ft.) Note: - Bluetooth SPP License (KWD-5003BT) is NOT required for both KCH-21RM and connected RF Decks. KCH-21RM has built-in Bluetooth SPP license that will also activate the connected RF Decks.	•	•	•	-	-	-
KCH-21RM-S	Hand Held Control Head with Short Cable (4 ft.) Note: - Bluetooth SPP License (KWD-5003BT) is NOT required for both KCH-21RM and connected RF Decks. KCH-21RM has built-in Bluetooth SPP license that will also activate the connected RF Decks.	•	•	•	-	-	-
KRK-15BM	Control Head Remote Kit Note: For mid power mobiles (NX-5700/5700B/5800/5800B/5900/5900B) only.	•	-	-	-	-	-
KRK-18HM	Interface Kit for a Control Head Note: Remote Control Cable must be purchased separately.	-	-	-	•	•	-
KRK-19BM	Interface Kit for an RF Deck Note: Remote Control Cable must be purchased separately.	-	-	-	•	•	-
REMOTE & MULTI RF DECK CABLES		NX-5700/5800/5900	NX-5700H/5800H	NX-5600H	NX-3720HG/3820HG	NX-3920G/3921G	NX-1700/1800
KCT-71M2	Remote Control Cable (17 feet)	•	•	•	•	•	-
KCT-71M3	Remote Control Cable (25 feet)	•	•	•	•	•	-
KCT-71M4	Remote Control Cable (1.6 feet)	•	•	•	•	•	-
KCT-71A50	KCT-71A Extended Control Head Cable (up to 50 ft. max.) Note: Please specify exact length at 1ft. increments when ordering. Caution: Extended control head cables exhibit a loss in speaker audio power to the control heads.	•	•	•	•	•	-
KCT-71A100	KCT-71A Extended Control Head Cable (up to 100 ft. max.) Note: Please specify exact length at 1ft. increments when ordering. Caution: Extended control head cables exhibit a loss in speaker audio power to the control heads.	•	•	•	•	•	-
KCT-77M2	Remote Control Cable for KCH-21RM (17 feet)	•	•	•	-	-	-

Optional Accessories for Kenwood Mobiles

OTHER ACCESSORIES		NX-5700/5800/5900	NX-5700H/5800H	NX-5600H	NX-3720HG/3820HG	NX-3920G/3921G	NX-1700/1800
KCT-46	Ignition sense cable Note: For mid power mobiles (NX-5700/5700B/5800/5800B/5900/5900B) only.	●	-	-	-	-	-
KCT-18	Ignition sense cable	●	●	●	●	●	●
KAP-2	Horn Alert/P.A. Relay Option Note: For mid power mobiles (NX-5700/5700B/5800/5800B/5900/5900B) only.	●	-	-	-	-	-
KCT-72M	External Accessory Connection Cable for KCH-19M / KCH-20RM / KRK-18HM	●	●	●	●	●	-
KLF-2	Line Filter (suppresses alternator whine, 25dB, 25A max).	●	●	●	●	●	●
KMB-10	Key lock adapter	●	-	-	●	●	●
KRA-40GM	GPS Antenna	●	●	●	●	●	-
KCT-90USB	USB Mobile Cable for SD Card Direct Access Support	●	●	●	-	-	-
KCT-91MRS	DB25 Cable for Mobile Relay Station (Conventional Only) Note: - Mobile Relay Station requires Multi RF Deck Configuration. - Built-in GPS and Bluetooth are not available with Mobile Relay Station. - DMR mode is not available	●	●	●	-	-	-
KWD-AE30K	AES FIPS140-2 Level 1 & DES Encryption Module (Multi-Key) Order a Labor Code L-5007 if installation is required. KWD-AE30K requires a Motorola KVL3000 Plus/4000 key loader device. KWD-AE30K is an U.S. DOC/BIS Export Controlled Item (ECCN 5A002A.1) Note: Required for Link Layer Authentication	●	●	●	-	-	-
KWD-AE31K	AES & DES Encryption Module (Multi-Key) Order a Labor Code L-5008 if installation is required. Note: Requires KPG-AE1/DE1 software key loader or Motorola KVL3000 Plus/4000 key loader device. KWD-AE31K is an U.S. DOC/BIS Export Controlled Item (ECCN 5A002A.1) Note: Required for Link Layer Authentication	●	●	●	-	-	-
KPG-115	Encryption Key Loader Interface Cable for Motorola KVL-3000/3000 Plus/4000	●	●	●	-	-	-
KPG-115AUT	KVL-4000 Radio Authentication Cable Note: Only capable for P25 Radio Authentication. Not available for Encryption Key Loading.	●	●	●	-	-	-
KPG-46XM	Full Speed USB Programming interface cable Note: This cable with USB mode may be used for SD Card Direct Access.	●	●	●	●	●	●
KPG-CLN-RJ45	Mobile-to-Mobile Cloning Cable (RJ45:RJ45), 3m	●	-	-	-	-	-
KCT-60M	DB15-to-15pin Molex Adapter Cable	-	-	-	●	●	●
GPS15XL-W	Garmin Internal GPS Receiver Board for NEXEDGE/FleetSync AVL Note: • Conventional operation only. • Requires GA25 MCX GPS antenna. • Refer to www.garmin.com for GPS-15XL-W technical specifications. • Option: Order L-1874 for Kenwood Long Beach installation.	-	-	-	-	-	●
GA25MCX	Garmin On-dash Style Magnetic base GPS Antenna for GPS15XL-W Note: shipped loose only; Install GA25MCX antenna to GPS15XL-W before vehicle install.	-	-	-	-	-	●